

Harxon HX-CVX600A Antenna

Harxon
a *BDStar* company

RELIABLE AND RUGGEDIZED WITH MILLIMETER ACCURACY

The Harxon HX-CVX600A GNSS antenna is designed with ruggedized enclosure that allows the antenna to be used in high shock and vibration environments. HX-CVX600A could provide the millimeter level accuracy with the advanced filtering capabilities and robust signal tracking. It is ideal for all surveying and I-construction machining applications.



CONSISTENT PERFORMANCE ACROSS FULL FREQUENCY BANDS

The Harxon HX-CVX600A offers full support for reliable and consistent satellite signals tracking, including GPS, GLONASS, Galileo and BeiDou, QZSS, IRNSS, SBAS as well as L-Band correction services. Additionally, it exhibits a very stable phase center variation with advanced multipoint feeding technology, exceptional low elevation satellite tracking with symmetric radiation patterns, high gain with ultralow signal loss, as well as outstanding wide-angle circular polarization (WACP) ensures excellent positioning accuracy.

RUGGEDIZED ENCLOSURE FOR TOUGH ENVIRONMENTS

The HX-CVX600A antenna, with its compact design, is built into a ruggedized IP69K rating housing with independent aerodynamic enclosure to withstand exposure against dust, rain, splash or sunlight. Standard TNC female connector with anti-collision cap design ensures optimal reliability in challenging environment.

STRONG ANTI-INTERFERENCE PERFORMANCE

The HX-CVX600A antenna equips a robust pre-filtered LNA to minimize de-sensing from high level out-of-band signals, and restraints possible electromagnetic interferences, offering strong anti-interference performance for consistent and reliable GNSS signals.

KEY FEATURES

- Comprehensive GNSS support: GPS, GLONASS, Galileo, BeiDou and QZSS, IRNSS, SBAS as well as L-Band correction services
- Millimeter PCV repeatability($\leq 2\text{mm}$)
- Improved signal filtering and excellent multipath rejection
- Ruggedized enclosure for tough environments

Harxon HX-CVX600A Antenna

PERFORMANCE

Signal Received

Upper Band	1.525 to 1.615 GHz
Lower Band	1.165 to 1.278 GHz
GPS	L1/L2/L5
GLONASS	L1/L2/L3
GALILEO	E1/E5a/E5b/E6
BDS	B1/B2/B3
QZSS	L1/L2/L3/L6
IRNSS	L5
SBAS	L1/L5
L-Band	

Nominal Impedance

50Ω

Polarization

RHCP

Axial Ratio

≤3dB

Azimuth Coverage

360°(omni-directional)

Output VSWR

≤2.0

Peak Gain

5.5dBi

LOW NOISE AMPLIFIER

LNA Gain

40±2dB

Noise Figure

≤2dB

Output VSWR

≤2.0

Passband Ripple

±2dB

Operation Voltage

+3.3~+18VDC

Operation Current

≤45mA

Differential Propagation Delay

≤5ns

MECHANICAL

Dimensions

φ150×53mm

Connector

TNC Female

Weight

≤600g

Vibration

9.8gRMS, 24-2000Hz

Shock

75Gs, 6ms duration, 3 shocks in mutually perpendicular axes

Salt Fog

96h (continuous spray, 5% concentration, 35°C)

Mounting

Pole Mount

Coarse threaded 5/8"-11, thread hole depth 10-11mm

Screws Mount

4x M8 screws depth

ENVIRONMENTAL

Temperature

Operating

-45°C~+85°C

Storage

-55°C~+85°C

Humidity

95% no-condensing

Water/Dust Resistance

IP67, IP69K

For the most recent details of this product:

<https://en.harxon.com/products-detail.php?Proid=179>

en.harxon.com

sales@harxon.com

9/F, Block B, Building D3, TCL International E City, NO.1001 Zhongshanyuan Road, Nanshan District, Shenzhen, China

Tel: +86-755-26989948


Fax: +86-755-26989994

Version 1 Specifications subject to change without notice.

©2020 Harxon Corporation. All rights reserved.

Printed in China
April 2020

Structure & Phase Center Drawing (mm)



Undeclared Tolerance: ±0.3mm